

PRODUCT DECLARATION / SAFETY DECLARATION — Asbestshop 163V (FFP3 NR D Respirator)

1. Product Information

- **Product name:** Asbestshop 163V (FFP3 NR D Respirator)
 - **Packaging options:** 1 piece / box of 15 / box of 180
 - **Brand / Supplier:** Asbestshop
 - **Application:** High-efficiency disposable filtering half mask for protection against hazardous airborne particulates, including fine dust, aerosols, and biological contaminants.
-

2. Product Description

The Asbestshop 163V is a single-use **FFP3 NR D** filtering half mask equipped with a high-quality exhalation valve for improved comfort and reduced breathing resistance.

The mask is intended for environments where maximum particulate filtration is required. It offers the highest protection class within EN 149:2001+A1:2009 for filtering half masks.

The product meets the general usage principles described in standard FFP3 respirator user information sheets, including correct facial fit, seal checks, and single-shift usage.

3. Key Features & Properties

- **Protection class:** FFP3 NR D (non-reusable, passes dolomite clogging test)
 - **Standards:**
 - EN 149:2001+A1:2009
 - PPE Regulation (EU) 2016/425 — Category III
 - **Design features:**
 - Multi-layer filter media
 - Integrated exhalation valve
 - Adjustable nose clip for optimal sealing
 - Dual elastic head straps for stable fit
 - Soft, comfortable inner lining
 - **Intended use:**

Effective protection against fine dust, hazardous particulates, aerosols and biological contaminants.
-

4. Usage & Handling (Summary)

- Ensure a proper facial seal before entering the hazard zone.
- Do not use with beards or facial hair that prevents proper sealing.
- The mask is **single-shift (NR)** → replace after each work shift, or sooner if damaged or breathing resistance increases.
- Leave the contaminated area immediately if breathing becomes difficult, dizziness occurs, or the mask is compromised.
- Always combine with protective clothing, gloves and eye protection when required.
- Minimum oxygen requirement: do not use in atmospheres below 19.5% oxygen.
- Does **not** offer protection against gases or vapours.

(These usage principles are consistent with standard FFP3 respirator instructions.)

5. Health & Safety Information

- The respirator **contains no asbestos** and does not release hazardous fibres.
- Correct fit and sealing are essential for proper protection.
- Not suitable for explosive atmospheres or oxygen-deficient environments.
- Replace immediately if damaged, wet, or contaminated.

6. Environmental & Waste Disposal

- Shelf life: up to **5 years** when stored clean, dry and protected from sunlight.
- Dispose of used masks according to local regulations.
- If used during asbestos work, treat as asbestos-contaminated waste.

7. Supplier Declaration

Asbestshop declares that the "Asbestshop 163V (FFP3 NR D)" respirator meets the requirements of EN 149:2001+A1:2009 and EU Regulation 2016/425 (Category III PPE).

When used according to the instructions, it provides high-efficiency respiratory protection in environments containing hazardous airborne particulates.

Place: Ittervoort – NL

Date: 27-11-2025

Name: Robert Peeters

Position: DGA

Signature:



Asbestshop

Beneluxstraat 2a

NL – www.asbestshop.nl – info@asbestshop.nl

DE – www.asbestshop.de – info@asbestshop.de

FR – www.asbestshop.fr – info@asbestshop.fr